



DECK LOADING TABLE

	A	B	C	D	E
TANKS	14,932 GAL	12,238 GAL	9,466 GAL	6,310 GAL	3,678 GAL
FODB1.C	98%	98%	98%	98%	98%
FOWING2.P/S	98%	50%	0%	0%	0%
FOWING3.P/S	98%	98%	98%	50%	0%
HOLD CARGO	BETWEEN A & B	BETWEEN B & C	BETWEEN C & D	BETWEEN D & E	
0 POUNDS TO 25,000 POUNDS	DO NOT OPERATE	DO NOT OPERATE	DO NOT OPERATE	DO NOT OPERATE	
25,000 POUNDS TO 50,000 POUNDS	5,000 POUNDS	DO NOT OPERATE	DO NOT OPERATE	DO NOT OPERATE	
50,000 POUNDS TO 100,000 POUNDS	17,000 POUNDS	3,000 POUNDS	NO DECK LOAD	DO NOT OPERATE	
100,000 POUNDS TO 150,000 POUNDS	22,000 POUNDS	15,000 POUNDS	15,000 POUNDS	8,000 POUNDS	
150,000 POUNDS TO 175,000 POUNDS	21,000 POUNDS	13,000 POUNDS	13,000 POUNDS	8,000 POUNDS	

Notes:

1. This deck loading table is subject to the restrictions listed in the attached "Operating Instructions".
2. Under icing conditions, reduce deck loads by 19,000 pounds. Do not operate where this reduction results in a negative deck load.
3. In the shaded conditions, freeboards may be less than 6", depending on deck and consumables loading. We recommend that loads be reduced to maintain 6" of freeboard.
4. Deck loads may not be carried on the shelter deck.
5. Allowable deck load includes both processing and codend loads.
6. Hold cargo weights include weight of any supplies or other gear carried in the freezer hold.

Figure 23

Deck Loading Table from ARCTIC ROSE Stability Booklet